

Aero-Maxx® II NFPA Lightbars



9188-1559-00

9188-1500 Series

This lightbar meets NFPA 1901 upper Zone "A" requirements for both clearing and blocking modes. When combined with our versatile Diamondback perimeter warning lamps and LED beacons, a 100% NFPA certified Weldon warning lamp package can be provided! Permanent lightbar is standard with mounting hardware optional. Lightbar gutter mounting kits available separately.

- Intense LED lighthoods provide a wide output coverage area exceeding NFPA requirements
- Rugged aluminum chassis and impact resistant polycarbonate lenses provide excellent durability in harsh environments
- Cover lenses available in clear or colored configurations to match the LED
- Slotted mounting bolt channels provide flexible mounting options
- Serviceable lenses, lighthoods and controller allow long-term maintenance of the product
- Additional options include: arrow stick, take-down and alley lights, and Opticom™ strobe tube

Order Nos.	Description
9188-1524L-00	24" length – perfect for split/aerial applications, lh
9188-1524R-00	24" length – perfect for split/aerial applications, rh
9188-1554-00	54" length
9188-1559-00	59" length
9188-1572-00	72" length



Diamondback™ Lightbars

The Diamondback lightbar utilizes our popular V37 Diamondback LED lamps to provide an unsurpassed warning signal for the vehicle. Available in body mount and roof mount configurations. Halogen scene/loading lights, strobe heads and DOT lighting can be incorporated into the lightbar using our 3800 Series lamps. The lightbar body is constructed of clear anodizing extruded aluminum providing excellent durability and corrosion protection.

- LED - low amp draw
- Integrated flasher
- Body or Roof Mount
- Split Bar Configurations for Aerials
- Straight, angle or wrap-around styles available



Order Nos.	Description
V3702-5935-00	8 Diamondback lightbar, R/R/SC/A/A/SC/R/R
V3702-6738-00	9 Diamondback lightbar, R/R/R/R/W/R/R/R/R
V3702-7434-00	10 Diamondback lightbar, R/R/R/R/W/W/R/R/R/R
V3713-8536-00	16 Diamondback wrap-around lightbar, red/wh

Custom configurations based on V34, V37 and 3800 Series Lamps available

3900 Series Lightbars

- LED - low amp draw
- Integrated flasher
- Body or Roof Mount
- Split Bar Configurations for Aerials
- Straight, angle or wrap-around styles available



Order Nos.	Description
3901-1604-00	LED, 2 lamp, roadside, red
3901-1605-00	LED, 2 lamp, curbside, red
3901-5903-00	Lightbar, 8 lamp
3902-7408-00	All LED, 10-lamp, all red
3902-7411-00	LED/halogen, 10-lamp, ems front, R/R/R/R/Ch/Ch/R/R/R/R
3902-8813-00	LED/scene, 12-lamp, ems rear, R/R/R/R/Sc/A/A/Sc/R/R/R/R
3902-8816-00	LED/halogen, 12-lamp, ems front, R/R/R/R/R/Ch/Ch/R/R/R/R/R
3910-7202-00	All LED, 14 lamp, red wrap around
3913-7218-00	All LED, 12-lamp wrap-around design, all red
3913-8501-00	All LED, 16-lamp wrap-around design, all red

Note: R=Red, C=Clear, A=Amber, Ch=Clear Halogen, Sc=Scene



7150-7160 Series LED Beacon

This high power LED beacon is perfect for upper rear warning applications. The lamp can be surface mounted or pole mounted. Available in red or amber.

- Eight 3 watt high power LEDs create an intense, attention grabbing signal
- Engineered reflector optics direct light efficiently into the required pattern
- Lamp includes 15 selectable flash patterns
- Coated die-cast aluminum housing protects against corrosion
- Replaceable Lens Cover provides lamp serviceability



7150-7160-10

Part Number	Description	SAE J1318
7150-7160-10	Red LED Beacon	Class 1
7150-7160-20	Amber LED Beacon	Class 1

7150-6000 Series 360° Roof Top Strobes

Our strobe lamp series is available in four styles: die cast or polycarbonate bases, low or high-lens configurations. The low-profile strobes are only 4.8" high and the high-profile strobes measures 6.7" in height

- Engineered for 12 and 24V applications
- Choice of polycarbonate or die cast base
- Easy three-screw mounting
- Computer-designed Fresnel optics
- Polycarbonate lens

Order Nos.	Description	Amp Draw 12V	SAE J1318
7150-6550-xx	Strobe, 7/10j, low-profile, poly base	1.3	Class 2
7150-6570-xx	Strobe, 7/10j, hi-profile, poly base	1.3	Class 2
7150-6640-xx	Strobe, 8/12j, low-profile, die cast base	1.3	Class 2
7150-6660-xx	Strobe, 8/12j, hi-profile, die cast base	1.3	Class 2
7150-6840-xx	Strobe, 12/16j, low-profile, die cast base	2.0/4.0	Class 1
7150-6860-xx	Strobe, 12/16j, hi-profile, die cast base	2.0/4.0	Class 1

Note: xx Denote (-10) red lens, (-20) amber lens, (-30) clear lens



7150-6640-10



7150-6860-20